



TYPICAL DRAWING NOT FOR CONSTRUCTION

**NOTES:**

Tank and Concrete lid manufactured for H2O loading.

Oil Capacity: 1280 liters  
Total Capacity: 2300 liters

Max recommended pipe size: 250mm

Design Parameters:  
Temp. 3 C Oil S.G. 0.85  
Influent Concrete. 100 mg/l  
Effluent Concrete. <10 mg/l  
Max flow 8mm Plates: 16 l/s

Lifting device type to be confirmed upon order.  
Supplied by others.

Checker Plate covers give better access for maintenance. Designed for occasional low speed (<10 km/h) traffic load.

Contact RWM for further details.

	PIPE SIZE	PIPE TYPE	INVERT
INLET			
OUTLET			
RIM ELEVATION			

Weights	
MAIN TANK	
CONCRETE LID	

**PROPIRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF RAINWATER MGNT. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RAINWATER MGNT. IS PROHIBITED.



CONTRACTOR:

PROJECT:

LOCATION:

MODEL NAME:  
RWM CPS TYPE 2- 8mm

DRAWN:

DATE CREATED:

LAST REVISION:

SCALE: 1:23